

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
9 September 2005 (09.09.2005)


PCT

(10) International Publication Number
WO 2005/082246 A1

- (51) International Patent Classification⁷: **A61B 5/06**
- (21) International Application Number:
PCT/IB2005/050467
- (22) International Filing Date: 4 February 2005 (04.02.2005)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
04100640.4 18 February 2004 (18.02.2004) EP
- (71) Applicant (for DE only): **PHILIPS INTELLECTUAL PROPERTY & STANDARDS GMBH** [DE/DE]; Stein-
damm 94, 20099 Hamburg (DE).
- (71) Applicant (for all designated States except DE, US):
KONINKLIJKE PHILIPS ELECTRONICS N. V.
[NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven
(NL).
- (72) Inventors; and
(75) Inventors/Applicants (for US only): **KRUEGER, Sascha** [DE/DE]; c/o Philips Intellectual Property & Standards GmbH, Weissshausstr. 2, 52066 Aachen (DE). **TIMINGER, Holger** [DE/DE]; c/o Philips Intellectual Property & Standards GmbH, Weissshausstr. 2, 52066 Aachen (DE). **SABCZYNSKI, Joerg** [DE/DE]; c/o Philips Intellectual Property & Standards GmbH, Weissshausstr. 2, 52066 Aachen (DE). **BORGERT, Joern** [DE/DE]; c/o Philips Intellectual Property & Standards GmbH, Weissshausstr. 2, 52066 Aachen (DE).
- (74) Agents: **VOLMER, Georg** et al.; Philips Intellectual Property & Standards GmbH, Weissshausstr. 2, 52066 Aachen (DE).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ,

[Continued on next page]

(54) Title: DEVICE AND METHOD FOR THE DETERMINATION OF THE POSITION OF A CATHETER IN A VASCULAR SYSTEM



(57) Abstract: The invention relates to a device and a method for the determination of the position of a catheter in a vascular system (8). In this, the measured positions ($\underline{r}_1, \underline{r}_2$) of two magnetic localizers at the tip of a catheter are displaced by correction vectors ($\underline{k}_1, \underline{k}_2$) while optimizing a quality dimension. The quality dimension includes a component taking account both of the deviation of the measured positions ($\underline{r}_1, \underline{r}_2$) from the vascular layout and of the deviation of the associated orientation ($\underline{r}_2 - \underline{r}_1$) from the orientation of the vascular layout according to a vascular map. In addition, the quality dimension may include components which evaluate the measured shape of the catheter compared to the vascular map. An additional correction step can further ensure that the corrected positions ($\underline{r}_1', \underline{r}_2'$) correspond to the preset fixed distance (d) of the localizers (4, 5).

WO 2005/082246 A1



TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(84) **Designated States** (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.